



# WALL AND FOOTING LAYOUT

SCALE: 1/4" = 1'-0"

**NOTE:**

- (1) WATERSTOPS SHALL BE PLACED AS FOLLOWS:
    - (a) AT ALL WALL AND FOOTING UNIONS
    - (b) AT ALL WALLS BETWEEN POURS FOR THE DAY, OR WHERE POURING OF CONCRETE IS INTERMITTENT AND NOT CONTINUOUS
    - (c) AT ALL AREAS WHERE POURING HAS BEEN INTERRUPTED AND FINAL SET MAY TAKE PLACE BEFORE POURING IS RESUMED.
  - (2) ALL WALLS ARE TO BE CENTERED ON FOOTINGS
  - (3) EXACT POSITIONS OF WALL THIMBLES TO BE LOCATED IN THE FIELD.
- SEE TYPED WATER STOP DETAIL SHEET NO.21 OF 23.

TYPICAL FOOTING DETAIL - SEE SHEETS 8 OF 23 AND 12 OF 23.

JOB: UPGRADING WASTEWATER TREATMENT FACILITIES  
 INCREMENT NO.1 FPA NO C 380325-03  
 CONTRACTOR'S RECORD DRAWINGS (AS BUILT)

DATE: SEPTEMBER 1976  
 REVISED

SHEET NO. 7 OF 23 SHEETS

SCALE: DRAWN BY: CHECKED BY:

Toman Engineering Company  
 Civil & Environmental Consultants  
 P. O. Box 708 P. O. Box 852  
 Mandan, ND - Bismarck, ND RKO OEO